



Notes:

1. Dimensions in mm
2. Compatible to both IR reflow soldering and TTW soldering
3. Pb free, ROHS Compliant

Optical Characteristics at Ta=25°C

Colour	Wavelength Distribution (nm)	λ dom (nm)	Total Flux @ IF=30mA, mlm (typ)	Luminous Intensity @ IF=30mA Iv (mcd)		Viewing Angle
				Min.	Max.	
Blue	464 - 476	470	600	140.0	285.0	120

Luminous intensity is measured with an accuracy of ± 11%

Electrical Characteristics at Ta=25°C

Vf @ If=30mA			Vr @ Ir=10uA
Min.(V)	Typ. (V)	Max. (V)	Min. (V)
3.05	3.4	4.0	5

Forward voltage, Vf is measured with an accuracy of ±0.1V

Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current.	30	mA
Peak pulse current; (tp ≤ 10 μs, Duty cycle = 0.005)	200	mA
Reverse voltage; Ir max= 10μA	5	V
LED junction temperature.	125	°C
Operating temperature.	-40 ... +100	°C
Storage temperature.	-40 ... +100	°C
Power dissipation (at room temperature)	135	mW

Radiation Pattern

