

24V LED Flex Strip Accessories



TKSFLCONT8KL3CH24VRF

8-Key 3-Channel Controller for RGB LED Flex Strip

- ◆ 8-Key Controller with synchronized RGB LED Indicators on main panel
- ◆ With RF Remote Control keypad
- ◆ L121 x W75 x H25 mm, with Screw terminals
- ◆ Output: 4A per channel; Output Power 288W 24V
- ◆ 25 Patterns with Play & Pause, Adjustable Speed & Brightness

7 Static Colours: Red, Green, Blue Yellow, Cyan, Magenta, White

3 or 7-colour discrete changes	3 or 7 colour gradual change	3-colour rapid change
7 fixed colour Strobe-flash	3 bi-colour cross-fade	Fade-out & Fade-in
Random Flashing	Auto change - all patterns	



TKSFLCONT8KL3CH24VRF

6-Key 3-Channel Controller for RGB LED Flex Strip

- ◆ RF 6-Key Controller
- ◆ With RF Remote Control keypad
- ◆ L130 x W40 x H31 mm, with Screw terminals
- ◆ Output: <3A per channel; Output Power 216W 24V
- ◆ 21 Patterns with Adjustable Speed & Brightness

7 Static Colours: Red, Green, Blue, Yellow, Cyan, Magenta, White

3 or 7 colour discrete changes	3 or 7 colour gradual change	7 fixed colour Strobe-flash
3 bi-colour cross-fade		



TKSFLDIMK1CH1224V12KIR

Constant Voltage Dimmer with Knob & Wireless IR Remote Keypad

- ◆ Single channel with Constant Voltage
- ◆ Illuminating Indicator for IR Remote Control
- ◆ 0 ~ 100% brightness control
- ◆ 256 level Grey scale, soft & smooth
- ◆ 4 shortcut settings 25%, 50%, 75%, 100%
- ◆ 4 DIY modes
- ◆ Power On/Off, & Delay Off button
- ◆ 12V ~ 24V DC input & output power
- ◆ Output: 6A, 75W (12V), 150W (24V)
- ◆ L87xW 87mm Switch; L86xW33mm Keypad



TKSFLDIMK1CH24V

Dimmer - Single Channel with Knob Control

- ◆ Knob control from OFF to full ON
- ◆ Step-less dimming
- ◆ L160 x W95 x H51 mm
- ◆ Screw terminals
- ◆ 4A rated current;
- ◆ 6A max load current



TKSFLAMPRGB24V4A

Amplifier - 3 Channel for RGB Lighting

- ◆ Amplifies 3 channel (Red, Green, Blue) output signals to increase capacity of system
- ◆ 3 CMOS Drain - Open outputs
- ◆ Connecting Mode: Common anode
- ◆ Rated Load Current: 4A each channel
- ◆ Max Load Current: 6A each channel
- ◆ L160 x W95 x H51 mm

TENROD

Making light work of electronic components

NSW Tel: 02 9748 0655 Fax: 02 9748 0258
VIC Tel: 03 9886 7800 Fax: 03 9886 7799
QLD Tel: 07 3879 2133 Fax: 07 3879 2188
Unit 1, 24 Vore Street, Silverwater, NSW 2128

E-mail: sales@tenrod.com.au
Website: www.tenrod.com.au