

ecoLED Tube The Better Alternative to Fluoros



- ☑ High Brightness & High Efficiency LEDs
- ☑ Environmentally friendly: mercury, lead free
- ☑ Robust Design against shock & vibrations
- ☑ No need for starters—no need to replace
- ☑ No need for ballast (ballast may remain)
- ☑ “4-foot” standard; 1200mm x 30mm
- ☑ No flickering
- ☑ Polycarbonate lens
- ☑ Aluminum casing
- ☑ IP 53 Rating; ~500gm net weight
- ☑ 240V AC 18W Operation
- ☑ 30,000 Hrs lifetime
- ☑ 120° Viewing Angle
- ☑ CRI > 75



Emitted Colour	Illumination (E) (1m)	Effective Illuminated Area (1m)	Flux (Lumens)
Daylight White (5600K—6300K)	~ 400 Lux	3.5m x 4.7m	~1500
White (4500K—5000K)	~ 400 Lux	3.5m x 4.7m	~1500
Warm White (3200K—3500K)	~ 350 Lux	3.5m x 4.7m	~1400

TENROD
Making light work for electronics manufacturing

Sydney: Tel. 02 9748 0655 Fax. 02 9748 0258
Melbourne: Tel. 03 9886 7800 Fax. 03 9886 7799
Brisbane: Tel. 07 3879 2133 Fax. 07 3879 2188

E-mail: sales@tenrod.com.au
Website: www.tenrod.com.au

Subject to change without notice