

ecoLED Tube

The Better Alternative to Fluoros



- ☑ High Brightness & High Efficiency LEDs
- ☑ Eco-friendly: mercury free, lead free
- ☑ Robust Design against shock & vibrations
- ☑ No starters - no replacements needed
- ☑ No need for ballast *
- ☑ "4-foot" standard; 1200mm x 30mm
- ☑ No flickering
- ☑ Polycarbonate lens (no glass)
- ☑ Aluminum casing (no breakages)
- ☑ IP 53 Rating; ~500gm net weight
- ☑ 240V AC 18W Operation
- ☑ 50,000 Hours Life Expectancy
- ☑ 120° Viewing Angle
- ☑ CRI > 75
- ☑ IES Data available



* Ferromagnetic or Iron-core ballast may remain; electronic ballast must be removed

Emitted Colour	Illumination (E) (1m)	Effective Illuminated Area (1m)	Flux (Lumens)
Daylight White (5600K—6300K)	~ 400 Lux	3.5m x 4.7m	~1500
FS White (4500K—5000K)	~ 400 Lux	3.5m x 4.7m	~1500
Cool White (3800K—4200K)	~ 375 Lux	3.5m x 4.7m	~1400
Warm White (3200K—3500K)	~ 360 Lux	3.5m x 4.7m	~1350

TENROD

Serving you with 20 years of LED experience

Sydney: Tel. 02 9748 0655 Fax. 02 9748 0258
 Melbourne: Tel. 03 9886 7800 Fax. 03 9886 7799
 Brisbane: Tel. 07 3879 2133 Fax. 07 3879 2188
 Auckland: Tel. 09 298 4346 Fax. 09 353 1317

E-mail: sales@tenrod.com.au
 Website: www.tenrod.com.au

Subject to change without notice